Page 2 of 8

AMENDMENTS TO THE CLAIMS

- 1. (Cancelled)
- 2. (Currently Amended) A ventilating device comprising:
- a housing having an outdoor air passage and an indoor air passage;
- a shaft rotatably supported by the housing, the shaft being rotatable about an axis which is substantially perpendicular to a direction of an air flow flowing in at least one of the outdoor air passage and the indoor air passage; and
- a plurality of heat exchanging elements mounted at around an outer circumferential surface of the shaft, the heat exchanging elements being rotatable on the shaft by the air flow to exchange heat between air in the outdoor air passage and air in the indoor air passage,

wherein a hub is formed at an outer circumferential surface of the shaft, in which an inner surface of the heat exchanging elements is mounted,

wherein each of the heat exchanging elements has substantially a same curved shape.

- 3. (Currently Amended) The ventilating device of claim 2, wherein the heat exchanging elements are mounted at the outer circumferential surface of the hub at regular intervals, each of the heat exchanging elements having substantially a same curved surface.
- 4. (Previously Presented) The ventilating device of claim 2, wherein a support rib is mounted at an outer circumferential surface of the heat exchanging elements.

Docket No.: 0630-2329PUS1

Reply to Office Action of April 10, 2007

Page 3 of 8

5. (Currently Amended) A ventilating device comprising:

a housing having an outdoor air passage and an indoor air passage;

a shaft rotatably supported by the housing, the shaft being rotatable about an axis which

is substantially perpendicular to a direction of an air flow flowing in at least one of the outdoor

air passage and the indoor air passage; and

a plurality of heat exchanging elements mounted at around an outer circumferential

surface of the shaft, the heat exchanging elements being rotatable on the shaft by the air flow to

exchange heat between air in the outdoor air passage and air in the indoor air passage,

wherein each of the heat exchanging elements has a concave surface and a convex

surface opposite to the concave surface, wherein when the concave surface faces an inlet of one

of the outdoor air passage and the indoor air passage, the convex surface faces an outlet of the

one of the outdoor air passage and the indoor air passage.

6. (Previously Presented) The ventilating device of claim 5, wherein the heat

exchanging element is made of non-woven fabric.

7. (Previously Presented) The ventilating device of claim 2, further comprising a

heat exchanging housing within the housing to communicate with the outdoor air passage and the

indoor air passage, the heat exchanging housing surrounding the heat exchanging elements.

8. (Currently Amended) A ventilating device comprising:

a housing having an outdoor air passage and an indoor air passage;

Page 4 of 8

a shaft rotatably supported by the housing, the shaft being rotatable about an axis which

is substantially perpendicular to a direction of an air flow flowing in at least one of the outdoor

air passage and the indoor air passage;

a plurality of heat exchanging elements mounted at-around an outer circumferential

surface of the shaft, the heat exchanging elements being rotatable on the shaft by the air flow to

exchange heat between air in the outdoor air passage and air in the indoor air passage;

a hub on the shaft; and

a support rib along an outer circumferential surface of the heat exchanging elements, each

of the heat exchanging elements extending from the hub to the support rib,

wherein each of the heat exchanging elements has substantially a same curved shape.

9. (Cancelled)

10. (Currently Amended) The ventilating device of elaim 9 claim 8, wherein each of

the heat exchanging elements has a concave surface.

11. (Previously Presented) The ventilating device of claim 10, wherein the air flow

flows onto the concave surface to rotate the heat exchanging elements.

12-14. (Cancelled)

JTE/GH/cl

Page 5 of 8

- (Previously Presented) The ventilating device of claim 2, wherein each of the heat 15. exchanging elements has a concave surface.
- 16. (Previously Presented) The ventilating device of claim 15, wherein the air flow flows onto the concave surface to rotate the heat exchanging elements.
- 17. (Previously Presented) The ventilating device of claim 2, wherein the outdoor air passage is parallel to the indoor air passage.
- (Previously Presented) The ventilating device of claim 2, wherein the axis is 18. perpendicular to the direction of the air flow.